

# AMSE U – Stamp Container External Visual Inspection Report per DOT SP-13341

Person performing inspection \_\_\_\_\_

**ORIGIN OF SHIPMENT:** \_\_\_\_\_ **DATE** \_\_\_\_\_

Customer name \_\_\_\_\_

Address \_\_\_\_\_

City/State/ZIP \_\_\_\_\_

## DESTINATION OF SHIPMENT

Company name \_\_\_\_\_

Bulk plant location \_\_\_\_\_

Address \_\_\_\_\_

City/State/ZIP \_\_\_\_\_

Tank manufacturer \_\_\_\_\_

Container serial number \_\_\_\_\_

Water capacity (WC) gallons \_\_\_\_\_

Estimated percentage of product in container \_\_\_\_\_

## TANK INSPECTION

**COMPLIES**

**FAILS**

- |   |                          |                          |
|---|--------------------------|--------------------------|
| 1. Shell/heads: condition of welds, dents, gouges, corrosion, abrasion.   | <input type="checkbox"/> | <input type="checkbox"/> |
| 2. Service valves and additional withdrawal valve for leakage, proper operation including handles and dome cover. | <input type="checkbox"/> | <input type="checkbox"/> |
| 3. Pressure relief devices; verify body of valve is not damaged, free of leaks and protective cover is in place.  | <input type="checkbox"/> | <input type="checkbox"/> |

REMARKS: defects found, location \_\_\_\_\_

**Tank disposition:**  Ready to transport

Removed product to 5%--Tank does not pass

**Lifting slugs and tie-down straps inspection:** Slings must be rated to a weight sufficient to accommodate the container and lading and shall comply with ASME B30.9 on slings used for lifting purposed. Lifting slings and tie-down straps must be visually inspected prior to each use. A sling showing tears, fraying or other signs of excessive wear must not be used. Knots are not permitted. Straps or chains used as tie-downs must be rated to exceed the maximum load to be transported and comply with the requirements of 49 CFR 393.100 through 393.106.

**COMPLIES**

**FAILS**

Condition of lifting slings

Condition of tie-down straps